

STANDARD DEPARTURE CHART -
INSTRUMENT (SID) RNP RWY 25 (AR)

ARP
13 26 27.37670 N 089 03 20.70584 W

CAT: A B C D
AD ELEV: 101 ft

APP 129.200
TWR 118.000

EL SALVADOR / EL SALVADOR INTL
SAN OSCAR ARNULFO ROMERO Y GALDAMEZ
(DUNEL2W, NAGEL2W, TUKOR2W)

DUNEL2W															
Designator	Path Descriptor	Fix Identifier (Waypoint Name)	Latitude	Longitude	Flyover	Course °M	Turn Direction	Altitude (ft)	Distance (Nm)	Speed Limit (Kt)	Magnetic Variation	Vertical Angle	Navigation Performance	Radius (NM)	Arc Center Fix
RNAV RNP RWY 25	IF	RW25	132645.2050N	0890230.7360W	-		-	-		-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	TF	LP800	132528.2730N	0890606.3620W	-	250	-	-	3.7	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	TF	LP502	132507.6270N	0890704.1990W	-	250	-	-	1.0	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	RF	LP802	132506.7130N	0891135.9410W	-	290	R	-	4.5	250	0°.00'E	-	RNP 0.3	6.5	LPC06 133115.6170N 0890921.3640W
RNAV RNP RWY 25	TF	DUNEL	134346.1760N	0900653.2580W	-	289	-	-	57.0	-	0°.00'E	-	RNP 1.0		

NAGEL2W															
Designator	Path Descriptor	Fix Identifier (Waypoint Name)	Latitude	Longitude	Flyover	Course °M	Turn Direction	Altitude (ft)	Distance (Nm)	Speed Limit (Kt)	Magnetic Variation	Vertical Angle	Navigation Performance	Radius (NM)	Arc Center Fix
RNAV RNP RWY 25	IF	RW25	132645.2050N	0890230.7360W	-		-	-		-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	TF	LP800	132528.2730N	0890606.3620W	-	250	-	-	3.7	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	TF	LP502	132507.6270N	0890704.1990W	-	250	-	-	1.0	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	RF	LP802	132506.7130N	0891135.9410W	-	290	R	-	4.5	-	0°.00'E	-	RNP 0.3	6.5	LPC06 133115.6170N 0890921.3640W
RNAV RNP RWY 25	RF	LP804	132557.7490N	0891315.2600W	-	306	R	-	1.8	-	0°.00'E	-	RNP 0.3	6.5	LPC06 133115.6170N 0890921.3640W
RNAV RNP RWY 25	TF	LP806	132715.2040N	0891505.1920W	-	306	-	-	2.2	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	RF	LP820	133401.3370N	0891701.0540W	-	024	R	-	7.6	250	0°.00'E	-	RNP 0.3	5.6	LPC07 133149.0870N 0891143.7080W
RNAV RNP RWY 25	TF	LP822	134315.7710N	0891259.5990W	-	024	-	-	10.0	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	RF	LP830	134613.5100N	0891046.0130W	-	050	R	-	3.7	-	0°.00'E	-	RNP 0.3	8.0	LPC08 134006.6870N 0890526.0380W
RNAV RNP RWY 25	TF	LP832	135931.7280N	0885447.2050W	-	050	-	-	20.4	-	0°.00'E	-	RNP 1.0	-	-
RNAV RNP RWY 25	TF	NAGEL	141541.3260N	0883629.3960W	-	048	-	-	24.0	-	0°.00'E	-	RNP 1.0	-	-

TUKOR2W															
Designator	Path Descriptor	Fix Identifier (Waypoint Name)	Latitude	Longitude	Flyover	Course °M	Turn Direction	Altitude (ft)	Distance (Nm)	Speed Limit (Kt)	Magnetic Variation	Vertical Angle	Navigation Performance	Radius (NM)	Arc Center Fix
RNAV RNP RWY 25	IF	RW25	132645.2050N	0890230.7360W	-		-	-		-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	TF	LP800	132528.2730N	0890606.3620W	-	250	-	-	3.7	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	RF	LP840	131628.7400N	0890702.4970W	-	122	L	-	11.2	-	0°.00'E	-	RNP 0.3	5.0	LPC12 132045.1810N 0890420.9460W
RNAV RNP RWY 25	RF	LP842	131556.3610N	0890548.6450W	-	107	L		1.3	250	0°.00'E	-	RNP 0.3	5.0	LPC12 132045.1810N 0890420.9460W
RNAV RNP RWY 25	TF	TUKOR	125238.8660N	0874904.2990W	-	107	-	-	78.4	-	0°.00'E	-	RNP 1.0	-	-