

STANDARD DEPARTURE CHART -
INSTRUMENT (SID) RNP RWY 25 (AR)

ARP
13 26 27.37670 N 089 03 20.70584 W

CAT: A B C D
AD ELEV: 101 ft
APP 129.200
TWR 118.000

EL SALVADOR / EL SALVADOR INTL
SAN OSCAR ARNULFO ROMERO Y GALDAMEZ
(KAPAN2W, URNOS2W, VITAN2W)

KAPAN2W															
Designator	Path Descriptor	Fix Identifier (Waypoint Name)	Latitude	Longitude	Flyover	Course °M	Turn Direction	Altitude (ft)	Distance (Nm)	Speed Limit (Kt)	Magnetic Variation	Vertical Angle	Navigation Performance	Radius (NM)	Arc Center Fix
RNAV RNP RWY 25	IF	RW25	132645.2050N	0890230.7360W	-		-	-		-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	TF	LP800	132528.2730N	0890606.3620W	-	250	-	-	3.7	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	TF	LP502	132507.6270N	0890704.1990W	-	250	-	-	1.0	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	RF	LP802	132506.7130N	0891135.9410W	-	290	R	-	4.5	-	0°.00'E	-	RNP 0.3	6.5	LPC06 133115.6170N 0890921.3640W
RNAV RNP RWY 25	RF	LP804	132557.7490N	0891315.2600W	-	306	R	-	1.8	250	0°.00'E	-	RNP 0.3	6.5	LPC06 133115.6170N 0890921.3640W
RNAV RNP RWY 25	TF	LP806	132715.2040N	0891505.1920W	-	306	-	-	2.2	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	TF	LP810	134442.4340N	0893955.3740W	-	306	-	-	29.8	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	RF	LP812	134810.7790N	0894301.3130W	-	332	R	-	4.6	-	0°.00'E	-	RNP 0.3	10.0	LPC11 135252.0630N 0893355.8990W
RNAV RNP RWY 25	TF	LP814	135517.0290N	0894651.8230W	-	332	-	-	8.0	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	TF	KAPAN	140308.6620N	0895159.9660W	-	327	-	-	9.3	-	0°.00'E	-	RNP 1.0	-	-

VITAN2W															
Designator	Path Descriptor	Fix Identifier (Waypoint Name)	Latitude	Longitude	Flyover	Course °M @	Turn Direction	Altitude (ft)	Distance (Nm)	Speed Limit (Kt)	Magnetic Variation	Vertical Angle	Navigation Performance	Radius (NM)	Arc Center Fix
RNAV RNP RWY 25	IF	RW25	132645.2050N	0890230.7360W	-		-	-		-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	TF	LP800	132528.2730N	0890606.3620W	-	250	-	-	3.7	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	RF	LP840	131628.7400N	0890702.4970W	-	122	L	-	11.2	-	0°.00'E	-	RNP 0.3	5.0	LPC12 132045.1810N 0890420.9460W
RNAV RNP RWY 25	RF	LP842	131556.3610N	0890548.6450W	-	107	L	-	1.3	-	0°.00'E	-	RNP 0.3	5.0	LPC12 132045.1810N 0890420.9460W
RNAV RNP RWY 25	RF	LP844	131621.1100N	0890152.7640W	-	061	L	-	4.0	250	0°.00'E	-	RNP 0.3	5.0	LPC12 132045.1810N 0890420.9460W
RNAV RNP RWY 25	TF	LP846	133132.1220N	0883335.3050W	-	061	-	-	31.4	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	RF	LP848	133202.9830N	0883230.2690W	-	067	R	-	1.2	-	0°.00'E	-	RNP 0.3	12.0	LPC13 132057.5970N 0882740.8990W
RNAV RNP RWY 25	TF	LP850	133400.9990N	0882746.8940W	-	067	-	-	5.0	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	TF	VITAN	135150.7920N	0874453.4870W	-	067	-	-	45.4	-	0°.00'E	-	RNP 1.0	-	-

URNOS2W															
Designator	Path Descriptor	Fix Identifier (Waypoint Name)	Latitude	Longitude	Flyover	Course °M @	Turn Direction	Altitude (ft)	Distance (Nm)	Speed Limit (Kt)	Magnetic Variation	Vertical Angle	Navigation Performance	Radius (NM)	Arc Center Fix
RNAV RNP RWY 25	IF	RW25	132645.2050N	0890230.7360W	-		-	-		-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	TF	LP800	132528.2730N	0890606.3620W	-	250	-	-	3.7	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	TF	LP502	132507.6270N	0890704.1990W	-	250	-	-	1.0	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	RF	LP802	132506.7130N	0891135.9410W	-	290	R	-	4.5	-	0°.00'E	-	RNP 0.3	6.5	LPC06 133115.6170N 0890921.3640W
RNAV RNP RWY 25	RF	LP804	132557.7490N	0891315.2600W	-	306	R	-	1.8	-	0°.00'E	-	RNP 0.3	6.5	LPC06 133115.6170N 0890921.3640W
RNAV RNP RWY 25	TF	LP806	132715.2040N	0891505.1920W	-	306	-	-	2.2	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	RF	LP820	133401.3370N	0891701.0540W	-	023	R	-	7.6	250	0°.00'E	-	RNP 0.3	5.6	LPC07 133149.0870N 0891143.7080W
RNAV RNP RWY 25	TF	LP822	134315.7710N	0891259.5990W	-	023	-	-	10.0	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	TF	LP824	135953.5680N	0890544.1830W	-	023	-	-	18.0	-	0°.00'E	-	RNP 0.3	-	-
RNAV RNP RWY 25	TF	URNOS	141907.4970N	0885720.7460W	-	023	-	-	20.8	-	0°.00'E	-	RNP 1.0	-	-