

Designator	Path Descriptor	Fix Identifier (Waypoint Name)	Latitude	Longitude	Flyover	Fix Role	Course °M	Turn Direction	Altitude (ft)	Distance (Nm)	Speed Limit (Kt)	Magnetic Variation	Vertical Angle	Navigation Performance	Radius (NM)	Arc Center Fix
RNAV RNP Y RWY 25	IF	LP555	130128.5740N	0881308.7950W		IAF			+3000			0°.00'E		RNP 1.0		
RNAV RNP Y RWY 25	TF	LP630	130848.4480N	0883502.3420W			289			22.6		0°.00'E		RNP 0.3		
RNAV RNP Y RWY 25	RF	LP628	131029.9430N	0883756.7120W			313	R		3.3		0°.00'E		RNP 0.3	8.0	LPC72 131624.7760N 0883223.5610W
RNAV RNP Y RWY 25	TF	LP616	132521.7400N	0885428.0850W			313		@3000	21.9		0°.00'E		RNP 0.3		
Designator	Path Descriptor	Fix Identifier (Waypoint Name)	Latitude	Longitude	Flyover	Fix Role	Course °M	Turn Direction	Altitude (ft)	Distance (Nm)	Speed Limit (Kt)	Magnetic Variation	Vertical Angle	Navigation Performance	Radius (NM)	Arc Center Fix
RNAV RNP Y RWY 25	IF	LP544	125146.8640N	0881712.7560W		IAF			+3000			0°.00'E		RNP 1.0		
RNAV RNP Y RWY 25	TF	LP628	131029.9430N	0883756.7120W			313			27.5		0°.00'E		RNP 0.3		
RNAV RNP Y RWY 25	TF	LP616	132521.7400N	0885428.0850W			313		@3000	21.9		0°.00'E		RNP 0.3		
Designator	Path Descriptor	Fix Identifier (Waypoint Name)	Latitude	Longitude	Flyover	Fix Role	Course °M	Turn Direction	Altitude (ft)	Distance (Nm)	Speed Limit (Kt)	Magnetic Variation	Vertical Angle	Navigation Performance	Radius (NM)	Arc Center Fix
RNAV RNP Y RWY 25	IF	LP616	132521.7400N	0885428.0850W		FAF			@3000			0°.00'E		RNP 0.3		
RNAV RNP Y RWY 25	TF	LP614	132710.4440N	0885629.1490W			313			2.7		0°.00'E	-3.000	RNP 0.3		
RNAV RNP Y RWY 25	RF	LP602	132747.0810N	0885937.1770W			250	L		3.3		0°.00'E	-3.000	RNP 0.3	3.0	LPC70 132457.2010N 0885833.9850W
RNAV RNP Y RWY 25	TF	RW25	132645.2050N	0890230.7360W	Y	MAPT	250		@151	3.0		0°.00'E	-3.000	RNP 0.3		
Designator	Path Descriptor	Fix Identifier (Waypoint Name)	Latitude	Longitude	Flyover	Fix Role	Course °M	Turn Direction	Altitude (ft)	Distance (Nm)	Speed Limit (Kt)	Magnetic Variation	Vertical Angle	Navigation Performance	Radius (NM)	Arc Center Fix
RNAV RNP Y RWY 25	TF	RW25	132645.2050N	0890230.7360W	Y	MAPT	250		@151	3.0		0°.00'E	-3.000	RNP 0.3		
RNAV RNP Y RWY 25	TF	LP502	132507.6270N	0890704.1990W			250			4.7		0°.00'E		RNP 1.0		
RNAV RNP Y RWY 25	RF	LP690	131702.4380N	0890906.9720W			138	L		9.8		0°.00'E		RNP 1.0	5.0	LPC69 132024.5410N 0890518.7670W
RNAV RNP Y RWY 25	TF	LP533	130001.7800N	0885325.9250W			138		+3000	22.8		0°.00'E		RNP 1.0		
RNAV RNP Y RWY 25	HM	LP533	130001.7800N	0885325.9250W	Y		002	L	+3000		230.00 KT	0°.00'E		NA		
Designator	Path Descriptor	Fix Identifier (Waypoint Name)	Latitude	Longitude	Flyover	Fix Role	Course °M	Turn Direction	Altitude (ft)	Distance (Nm)	Speed Limit (Kt)	Magnetic Variation	Vertical Angle	Navigation Performance	Radius (NM)	Arc Center Fix
RNAV RNP Y RWY 25	TF	LP533	130001.7800N	0885325.9250W		IAF	138		+3000	22.8		0°.00'E		RNP 0.3		
RNAV RNP Y RWY 25	TF	LP622	132131.1680N	0885248.5150W			002			21.4		0°.00'E		RNP 0.3		
RNAV RNP Y RWY 25	RF	LP616	132521.7400N	0885428.0850W			313	L	@3000	4.300		0°.00'E		RNP 0.3	5.0	LPC71 132139.6860N 0885756.1290W
RNAV RNP Y RWY 25	IF	LP616	132521.7400N	0885428.0850W		FAF			@3000			0°.00'E		RNP 0.3		
RNAV RNP Y RWY 25	TF	LP614	132710.4440N	0885629.1490W			313			2.7		0°.00'E	-3.000	RNP 0.3		
RNAV RNP Y RWY 25	RF	LP602	132747.0810N	0885937.1770W			250	L		3.3		0°.00'E	-3.000	RNP 0.3	3.0	LPC70 132457.2010N 0885833.9850W
RNAV RNP Y RWY 25	TF	RW25	132645.2050N	0890230.7360W	Y	MAPT	250		@151	3.0		0°.00'E	-3.000	RNP 0.3		

CHANGES: LP533 FO VALUE Y