

CHANGES: LP533 FO VALUE Y

Designator	Path Descriptor	Fix Identifier (Waypoint Name)	Latitude	Longitude	Flyover	Fix Role	Course °M	Turn Direction	Altitude (ft)	Distance (Nm)	Speed Limit (Kt)	Magnetic Variation	Vertical Angle	Navigation Performance	Radius (NM)	Arc Center Fix
RNAV RNP Z RWY 25	IF	AMESA	133717.1280N	0894412.7670W		IAF			+3300			0°.00'E		RNP 1.0		
RNAV RNP Z RWY 25	TF	LP619	133345.3200N	0892856.1330W			103			15.3		0°.00'E		RNP 0.3		
RNAV RNP Z RWY 25	TF	LP618	133239.4680N	0892459.3120W			106		+3300	4.0		0°.00'E		RNP 0.3		
RNAV RNP Z RWY 25	RF	LP612	133214.3320N	0892050.3440W			086	L		4.1		0°.00'E		RNP 0.3	11.7	LPC68 134358.2900N 0892141.8480W
RNAV RNP Z RWY 25	TF	LP608	133337.3020N	0890053.3250W			086			19.5		0°.00'E		RNP 0.3		
RNAV RNP Z RWY 25	RF	LP606	133241.3900N	0885826.3530W			137	R	@3000	2.6		0°.00'E		RNP 0.3	3.0	LPC66 133036.9560N 0890040.3940W
Designator	Path Descriptor	Fix Identifier (Waypoint Name)	Latitude	Longitude	Flyover	Fix Role	Course °M	Turn Direction	Altitude (ft)	Distance (Nm)	Speed Limit (Kt)	Magnetic Variation	Vertical Angle	Navigation Performance	Radius (NM)	Arc Center Fix
RNAV RNP Z RWY 25	IF	LP522	134242.3230N	0894044.2790W		IAF			+8100			0°.00'E		RNP 1.0		
RNAV RNP Z RWY 25	TF	LP620	133528.2650N	0893211.0480W			131			11.0		0°.00'E		RNP 0.3		
RNAV RNP Z RWY 25	RF	LP619	133345.3200N	0892856.1330W			106	L		3.6		0°.00'E		RNP 0.3	8.3	LPC67 134146.3620N 0892636.3670W
RNAV RNP Z RWY 25	TF	LP618	133239.4680N	0892459.3120W			106		+3300	4.0		0°.00'E		RNP 0.3		
RNAV RNP Z RWY 25	RF	LP612	133214.3320N	0892050.3440W			086	L		4.1		0°.00'E		RNP 0.3	11.7	LPC68 134358.2900N 0892141.8480W
RNAV RNP Z RWY 25	TF	LP608	133337.3020N	0890053.3250W			086			19.5		0°.00'E		RNP 0.3		
RNAV RNP Z RWY 25	RF	LP606	133241.3900N	0885826.3530W			137	R	@3000	2.6		0°.00'E		RNP 0.3	3.0	LPC66 133036.9560N 0890040.3940W
Designator	Path Descriptor	Fix Identifier (Waypoint Name)	Latitude	Longitude	Flyover	Fix Role	Course °M	Turn Direction	Altitude (ft)	Distance (Nm)	Speed Limit (Kt)	Magnetic Variation	Vertical Angle	Navigation Performance	Radius (NM)	Arc Center Fix
RNAV RNP Z RWY 25	IF	LP606	133241.3900N	0885826.3530W		FAF			@3000			0°.00'E		RNP 0.3		
RNAV RNP Z RWY 25	RF	LP602	132747.0810N	0885937.1770W			250	R		5.9		0°.00'E	-3.000	RNP 0.3	3.0	LPC66 133036.9560N 0890040.3940W
RNAV RNP Z RWY 25	TF	RW25	132645.2050N	0890230.7360W	Y	MAPT	250		@151	3.0		0°.00'E	-3.000	RNP 0.3		
Designator	Path Descriptor	Fix Identifier (Waypoint Name)	Latitude	Longitude	Flyover	Fix Role	Course °M	Turn Direction	Altitude (ft)	Distance (Nm)	Speed Limit (Kt)	Magnetic Variation	Vertical Angle	Navigation Performance	Radius (NM)	Arc Center Fix
RNAV RNP Z RWY 25	TF	RW25	132645.2050N	0890230.7360W	Y	MAPT	250		@151	3.0		0°.00'E	-3.000	RNP 0.3		
RNAV RNP Z RWY 25	TF	LP502	132507.6270N	0890704.1990W			250			4.7		0°.00'E		RNP 1.0		
RNAV RNP Z RWY 25	RF	LP690	131702.4380N	0890906.9720W			138	L		9.8		0°.00'E		RNP 1.0	5.0	LPC69 132024.5410N 0890518.7670W
RNAV RNP Z RWY 25	TF	LP533	130001.7800N	0885325.9250W			138		+3000	22.8		0°.00'E		RNP 1.0		
RNAV RNP Z RWY 25	HM	LP533	130001.7800N	0885325.9250W	Y		002	L	+3000		230.00 KT	0°.00'E		NA		