

AREA CHART

TMA TONCONTIN

LEGEND																									
CONTROL AREA (TMA)(AWY)	—————																								
CONTROL ZONE (CTR)	— — —																								
REPORTING POINT (Compulsory)	▲																								
DISTANCE IN NM	< 55 NM >																								
MINIMUM FLIGHT ALTITUDE	12 000 ft																								
MAGNETIC BEARING	003°																								
<table> <tr> <td>RADIO NAVIGATION AID</td><td>NAME</td><td>TONCONTIN</td></tr> <tr> <td></td><td>NAVAID TYPE</td><td>VOR/DME</td></tr> <tr> <td></td><td>FREQUENCY</td><td>112.30 MHz</td></tr> <tr> <td></td><td>CHANNEL</td><td>CH 70X</td></tr> <tr> <td></td><td>IDENTIFICATION</td><td>TNT — — ● —</td></tr> <tr> <td></td><td>COORDINATES</td><td>140144. 1122N</td></tr> <tr> <td></td><td></td><td>0871344.7978W</td></tr> <tr> <td></td><td>ELEVATION DME ANTENNA</td><td>1230 M</td></tr> </table>		RADIO NAVIGATION AID	NAME	TONCONTIN		NAVAID TYPE	VOR/DME		FREQUENCY	112.30 MHz		CHANNEL	CH 70X		IDENTIFICATION	TNT — — ● —		COORDINATES	140144. 1122N			0871344.7978W		ELEVATION DME ANTENNA	1230 M
RADIO NAVIGATION AID	NAME	TONCONTIN																							
	NAVAID TYPE	VOR/DME																							
	FREQUENCY	112.30 MHz																							
	CHANNEL	CH 70X																							
	IDENTIFICATION	TNT — — ● —																							
	COORDINATES	140144. 1122N																							
		0871344.7978W																							
	ELEVATION DME ANTENNA	1230 M																							

Area minimum altitude (AMA)

Each 1° quadrilateral contains an area minimum altitude (AMA) which represents the lowest altitude which may be used under instrument meteorological conditions (IMC). The AMA provides a minimum clearance of 1000 ft (2000 ft in mountainous areas) above all obstacles in the quadrilateral. It is represented in thousands and tens of feet above mean sea level.

Example: 10400 feet

10⁴

